ORIGINAL

NEW APPLICATION





Office: 928-854-8800 Fax: 928-854-88714 OCT -6 P 12: 42
500 N. Lake Havasu Ave. Ste. C100
Lake Havasu City, Arizona 86403AZ CORP COMMISSION
DOCKET CONTROL

September 29, 2014

Arizona Corporation Commission DOCKETED

OCT 06 2014

Docket Control Arizona Corporation Commission 1200 West Washington Street Phoenix AZ 85007

W-02821A-14-0363

DOCKETED BY

Attached is an application by Double R Water Distributors, Inc. for approval of a Cross-Connection Tariff. The purpose of this tariff is to protect Double R Water Distributors, Inc. from the possibility of contamination caused by the backflow of contaminants that may be resent on the customer's premises.

Sincerely,

Todd R. Bremner

President

Enclosures:

Application for Cross-Connection or Backflow Tariff

CROSS-CONNECTION OR BACKFLOW TARIFF

PURPOSE:		

	The purpose of this tariff is to protect	DOUBLE	R WATER	R DIST	RIBUTORS	3,_
INC.	("Compan	y") wate	r from	the	possibility	of
contan	nination caused by the backflow of	contamina	ints that n	nay be	present on	the
custon	ner's premises by requiring the inst	allation ar	nd periodic	testing	g of backflo	ow-
preven	ation assemblies pursuant to the prov	visions of t	he Arizon	a Admi	nistrative C	ode
("A.A.	.C".) R14-2-405.B.6 and A.A.C. R18-4	4-215.				

REQUIREMENTS:

In compliance with the Rules of the Arizona Corporation Commission ("Commission") and the Arizona Department of Environmental Quality ("ADEQ"), specifically A.A.C. R14-2-405.B.6 and A.A.C. R18-4-215 relating to backflow prevention:

- 1. The Company may require a customer to pay for and to have installed a backflow-prevention assembly if A.A.C. R18-4-215.B or C applies.
- 2. A backflow-prevention assembly required to be installed by the customer under Paragraph 1 of this tariff shall comply with the requirements set forth in A.A.C. R18-4-215.D and E.
- 3. Subject to the provisions of A.A.C. R14-2-407 and 410, and in accordance with Paragraphs 1 and 7 of this tariff, the Company may terminate service or may deny service to a customer who fails to install a backflow-prevention assembly as required by this tariff
- 4. The Company shall give any existing customer who is required to install a backflow-prevention assembly written notice of said requirement. If A.A.C. R14-2-410.B.1.a. is **not** applicable, the customer shall be given thirty (30) days from the time such written notice is received in which to comply with this notice. If the customer can show good cause as to why he cannot install the backflow-prevention assembly within thirty (30) days, the Company or Commission Staff may suspend this requirement for a reasonable period of time.

FOR OFFICIAL USE ONLY

Effective 1	Date:
LIECTIVE	Jaic.

- 5. Testing shall be in conformance with the requirements of A.A.C. R18-4-215.F. The Company may require the customer to pay to have the backflow-prevention assembly tested as long as the Company does not require an unreasonable number of tests.
- 6. The customer shall provide the Company with records of installation and testing. For each backflow-prevention assembly, these records shall include:
 - a. assembly identification number and description;
 - b. location
 - c. date(s) of test(s);
 - d. description of repairs and recommendations for repairs made by tester;
 - e. the tester's name and certificate number.
- 7. In the event the backflow-prevention assembly does not function properly or fails any test, and an obvious hazard as contemplated under A.A.C. R14-2-410.B.1.a. exists, the Company may terminate service immediately and without notice. The backflow-prevention assembly shall be repaired or replaced by the customer and retested.
- 8. In the event the backflow-prevention assembly does not function properly or fails any test, or in the event that a customer fails to comply with the testing requirement, and A.A.C. R14-2-410.B.1.a. is **not** applicable, the backflow-prevention assembly shall be repaired or replaced within fourteen (14) days of the initial discovery of the deficiency in the assembly or its function. Failure to remedy the deficiency or dysfunction of the assembly, or failure to retest, shall be grounds for termination of water service in accordance with A.A.C. R14-2-410.

**FOR OFFICIAL USE ONLY	/ * *
-------------------------	-------

Effective	D-4
HITECTIVE	I)ate: